



## **Tuning Fork Crystal (SMD)**

## **Typical Applications:**

- Mobile Phone
- Digital Camera

- Portable PCs
- Wireless LAN

## CS7 (SMD Tuning Fork Series) Part Number: CS7-Freq-CL-TR Example: CS7-32.768KHz-12.5-TR



7	Dimension (Unit: mm)
_	<u>CS7</u>
	1 44 #3 1 1 6.7 #2 0.1 7.0 Max
-	
_	INTERNAL LEAD CONNECTION
	#4 #3 #1 #2
	RECOMMENDED SOLDERING PATTERN

Specification		CS7
Part No.	Example	Size
CS7-Freq-CL-TR	CS7-32.768KHz-12.5-TR	7.0 x 1.5 mm

Specification	CS7	
Frequency Range	32.768KHz	
Tolerance at 25°C	$\pm 10$ to $\pm 50$ ppm	
Turnover Temperature	+25°C	
Temperature Coefficient	(-0.035±0.01) x 10 <sup>-6</sup> /° C <sup>2</sup>	
Load Capacitance	7 to 12.5pF	
ESR	65KΩ Max.	
Aging (First Year)	±3ppm Max.	
Operating Temperature Range	-40°C to +85°C	
Storage Temperature Range	-55°C to +125°C	
Drive Level	1μW Max.	